



Selection Chart

Accredited Ground Anchor Fixing Methods for use with General Stones*

Accredited Fixing Systems		Memorial Height Category				
NAMM Ref No. NRN/	Manufacturer/Supplier Name of System	Category A Up to 900mm (3'0")	Category B Up to 1200mm (4'0")	Category C Up to 1500mm (5'0")	Category D Up to 1800mm (6'0")	Category E 50mm (2") base Up to 610/750mm (24/30")
C.C.A. Fixings						
101,102 & 105	Single Bar (700 x 24) set @ min. protrusion of 70, 95, or 48mm.	x	x			x (750) granite
103	Twin Bar (700 x 24)			x		
104	Triple Bar (700 x 24)				x	
Myatt & Leason Ltd						
201	Single Tube (600 x 38)	x	x			
202	Twin Tube (600 x 38)			x	x	
NAMM Fixings						
301	Kit A - 2x16mm dowels, tubes 460	x				
302	Kit B - 2x20mm dowels, tubes 460		x			
A.O.R. Stone Keel (S. Hill)						
401	Single Bar & Pin (600 x 25)	x	x			
402	Tube, Bar & Pin (600 x 33 & 25)		x			
403	Single Bar & Pin (400 x 25)					x (610) granite

Nettlebank Fixings						
601	Single bar (600 x 25) set @ 75mm	x				
603	Single bar (600 x 25) set @ 45mm					x (610) granite
604	Single Bar (750 x 25)		x			
The Blast Shop						
701,708	1 No. (600 x 38mm) Tube & Peg	x	x			
702	2 No. (600 x 38mm) Tube & Peg			x		
703,704	1 No. (600 x 38) Tube & Lockdown	x	x			
705	1 No. (600 x 28) Tube & Peg	x				
706	1 No. (585 x 26.9) Tube & Peg	x				
707	1 No. (580 x 26.9) Tube & lockdown	x				
709	1 No. (600x28) Tube & Peg 162 x 23/28 & Lockdown					x (610)
710	1 No. (600x28) Tube & Lockdown					x (610)
711	1 No. (600 x 28.6) Tube & Peg					x (610) granite
712	1 No. (448x28) Tube & Peg					x (610)
713	1 No. (448x28) Tube & Lockdown					x (610)
714	Firmalite foundation system, 585 x 28.6 tube & peg with Lockdown	x				
715	Firmalite system, 585 x 28.6 tube & peg, with Lockdown & 600 x 38 tube		x			
716	Concrete foundation system, 585 x 38 tube & peg with Lockdown		x			

General Stones are classed as all materials as hard or harder than marble.

NAMM Fixings are suitable for use with soft natural stones (e.g. Portland Stone) in Category A.